

Multiple stapler

«SR»



- **Special design for efficient and accurate stapling of caps (hangers).**
- **Simultaneous operation of max. 8 stapling heads.**
- **Heavy duty heads process staples of various lengths adapted to the cap thickness.**
- **Effortless and fast operation.**
- **Flawless and highly efficient stapling method.**

The roller mounted table, equipped with pull-back spring, prevents the fabric from shifting. Even «difficult» materials are processed quickly and accurately. Lateral position of stapling heads is easily adjustable; leaf springs provide for individual fixation. Cardboard caps are held in place by means of special holders. Substantially accelerated and simplified stapling process.

Technical Data

| | |
|--------------------------------------|---|
| Max. cap length | 500 mm (19½") |
| Max. cap width (folded) | 120 mm (4¾") |
| Max. distance between staple centres | 440 mm (17¼") |
| Min. distance between staple centres | 60 mm (2⅜") |
| Staple length: | 8, 10, 12, 14 mm (⁵ / ₁₆ ", ³ / ₈ ", ¹ / ₂ ", ⁹ / ₁₆ ") |
| Overall dimensions | length 790 mm (31") |
| | width 690 mm (27") |
| | height 330 mm (12") |
| Approx. weight (incl. 5 heads) | gross 32 kg (70 lb.) |
| | net 26 kg (57 lb.) |

Subject to design changes



- **Special design for efficient and accurate stapling of caps (hangers).**
- **Simultaneous operation of max. 8 stapling heads.**
- **Heavy duty heads process staples of various lengths adapted to the cap thickness.**
- **2-hand Safety Device.**
- **Effortless and fast operation.**
- **Flawless and highly efficient stapling method.**

Power operated model with roller mounted table and same characteristics as type SR. Stapling action starts after having pushed the two buttons and when table has been moved to its working position. Lateral position of stapling heads is easily adjustable, leaf springs provide for individual fixation. Cardboard caps are held in place by means of special holders. Machine requires no effort, operator can be seated. Extremely efficient and accurate working process.

Technical Data

| | |
|--------------------------------------|--|
| Max. cap length | 500 mm (19½") |
| Max. cap width (folded) | 120 mm (4¾") |
| Max. distance between staple centres | 440 mm (17¼") |
| Min. distance between staple centres | 60 mm (2⅜") |
| Staple length | 8, 10, 12, 14 mm (⅝", ⅜", ½", ⅞") |
| Stop motor | 0.18 kW |
| Electrics | 1 x 230 V / 50 cycles or 1 x 120 V / 60 cycles |
| Overall dimensions | length 790 mm (31") |
| | width 710 mm (27") |
| | height 1120 mm (42") |
| Table height above floor level | 900 mm (35½") |
| Approx. weight (incl. 5 heads) | gross 100 kg (220 lb.) |
| | net 78 kg (172 lb.) |

Subject to design changes